

Why Water Is Seeping Through Your Garage Door

Water leaking under a garage door is usually caused by a breakdown in the seal between the door and the floor, but the source may also be higher on the opening. An overhead garage door must close uniformly against the garage door frame, garage floor, and garage door threshold. If any of these surfaces are damaged, uneven, or inadequately sealed, rain can enter the garage.

The bottom weather seal is one of the most important parts of a water-resistant garage door. This flexible strip seals against the floor when the door closes. Over time, it can become fragile, split, flattened, or pulled out of its retainer. A damaged garage door panel can also allow water to pass through cracks, dents, separating joints, or damaged seams.

Water may enter at several locations:

- Under the door through a worn bottom weather seal
- At the sides through openings between the door and garage door frame
- Between panels through damaged joints or bent sections
- Across the garage door threshold where the concrete floor is irregular
- Above the opening if flashing, trim, or caulking has broken down

Finding the exact entry point is important. Replacing a seal will not fix the problem if water is actually coming through a cracked panel, a leaking garage door frame, or drainage running toward the opening.

Typical Causes of Garage Door Water Leaks in Los Angeles

Los Angeles County has a Mediterranean climate with long dry periods followed by rain during the winter season. Those months of intense sunshine and high temperatures can cause rubber seals and caulking to dry out or crack before the first major storm exposes an issue. During intense winter rain, even a small opening can allow substantial rainwater into a garage.

Wind-driven rain is especially problematic in Santa Monica, Venice, Long Beach, and other coastal communities. Strong gusts can force water beneath the door, through side gaps, and into small cracks around the garage door frame. Coastal exposure may also speed up deterioration of metal hardware, fasteners, and weather seals.

A sloped driveway is another frequent cause. Driveways are often designed to move water away from a home, but settlement, resurfacing, or poor grading can create a low point at the garage entrance. Water then pools beside the door instead of draining away. A standard seal may not stop water that is moving forcefully toward the opening with force.

Older homes in Northeast Los Angeles, South Los Angeles, and the San Fernando Valley may have aging garage doors, frames, concrete floors, or drainage systems. A door installed decades ago may no longer sit level, while the surrounding frame may have shifted or developed gaps. In these cases, garage door repair may need to be combined with threshold, frame, or drainage work.

Damaged Weatherstripping and Bottom Seals

Weatherstripping protects the edges and moving joints of a garage door. The garage door seal at the bottom is commonly made from pliable rubber or vinyl and slides into a channel along the lowest panel. A rubber gasket may become brittle, damaged, torn, or compressed for good after years of exposure.

When the seal no longer touches the floor across its full width, water can enter beneath the door. Homeowners often describe this as rain coming into the garage or water leaking under garage door panels. Gaps are particularly common at the corners, where the floor may be below the middle.

EM Garage Doors And Gate Service Inc

19629 Cantara St, Reseda, CA 91335

(818) 919-0785

<https://emgaragedoorsandgateservice.com/>

<https://maps.app.goo.gl/XujLWxA4pAQKARQT8>

34.2193569, -118.5613022

A correctly installed seal acts as a barrier against water, but it should not be relied upon to correct a extremely uneven floor. If the concrete slopes toward the garage, a garage door threshold seal can provide an further raised barrier. The threshold must be attached to a clean, dry surface and positioned so the door closes securely without too much pressure.

Inspect the weatherstripping along the sides and top as well. If it is slack, shriveled, or separated from the garage door frame, rain can enter even when the bottom seal is in good condition. A thoroughly sealed weatherproof garage door may require replacement of the bottom seal, side stops, top seal, and damaged caulking.

Cracked Panels, Misalignment, and Door Gaps

A damaged garage door panel can allow water through cracks, holes, dents, or damaged joints. Wood panels may absorb moisture and swell, while older steel panels can rust around fasteners and seams. Insulated panels may delaminate inside after impact or extended exposure to moisture.

Door alignment is also important. If the sections do not meet properly, one side may have a large gap against the floor or frame. Misalignment can result from damaged rollers, loose hinges, bent garage door tracks, broken cables, or a door that has shifted in its opening. A garage door inspection should evaluate how the door moves and the gaps rather than focusing only on visible holes.

Panel replacement may be suitable when one section has localized damage and matching parts remain available. However, replacing one panel on an older door can create differences in color, design, weight, or insulation. If several sections are damaged or the structure is badly warped, full garage door replacement may be a more practical option.

How to Inspect a Leaking Garage Door Safely

Begin with a careful examination during daylight and after rainfall if possible. Leave the door fully closed and look for daylight beneath or beside it. Check for wet tracks, water marks, peeling paint, swollen wood, rust, mold, and damp items stored near the opening. Tracing the highest wet point can help distinguish water intrusion from condensation or a plumbing leak.

For garage door safety, do not remove springs, cables, drums, hinges, or track hardware. Springs and cables hold significant tension, and a sudden release can cause severe injury. A torsion spring above the door is particularly dangerous to adjust without the correct tools and training.

With the door closed, examine the bottom weather seal for cracks, flattening, missing sections, and gaps. Inspect the threshold and concrete for cracks or low areas. Look at the garage door frame for deteriorated trim and failed caulking. If the door is safe to operate, watch it open and close from a distance. Stop using it if it binds, falls, makes grinding sounds, or moves unevenly.

Photograph water damage with photographs and note where water appears after different types of weather. This information helps a technician determine whether the problem is a seal, panel, frame, drainage, or alignment issue.

Garage door repair approaches for moisture infiltration

The right repair varies with the entry point. Bottom seal replacement is often the simplest solution when the seal is split or worn but the door and floor remain sound. The old strip is removed, the retainer is cleaned, and a correctly sized garage door bottom seal is fitted across the door.

If water runs toward the opening, a threshold seal may be installed on the garage floor. This creates a raised channel that pairs with the door's bottom seal. The floor must be properly dried and structurally suitable, and the threshold should not interfere with vehicles, walking paths, or the operation of the door.



Garage door panel repair may involve changing a damaged section, reinforcing a minor defect, or correcting a separated joint. Severe warping, rust, or impact damage usually calls for panel replacement rather than cosmetic patching. Caulking can cover stationary gaps around the garage door frame, but it should not be used to seal moving joints or conceal active structural problems.

Other repairs may include fixing garage door alignment, replacing rollers, adjusting tracks, repairing hinges, or improving the frame. If water is collecting because of the driveway or surrounding drainage, a garage door company may locate the issue, but concrete grading, drains, or waterproofing may require a separate licensed contractor.

When to Repair versus Replace a Garage Door Panel

Repair a garage door panel when the damage is limited, localized, and the section remains structurally sound. Replacement is more appropriate when the panel is separated, badly dented, rusted through, swollen, or no longer aligns with adjacent sections. A damaged panel can continue to let in water and may place extra stress on rollers and tracks.

Consider the age and condition of the complete door. If the existing door is outdated, poorly insulated, or has repeated failures, an insulated garage door can improve durability and help moderate temperatures inside the

garage. Matching a replacement panel may be difficult for discontinued models, making a new door more appealing.

Garage door replacement cost is determined by the construction material, dimensions, insulation level, design, fittings, disposal, and installation work. A less expensive panel repair may be reasonable for a recently installed door, while major panel damage on an aged door can make replacement a more valuable long-term value. Request a documented garage door repair estimate that explains both options.

Garage door repair Cost and Pricing in Los Angeles

Garage door repair cost in Los Angeles differs according to the source, door size, part availability, urgency, and access to the damaged area. A simple seal replacement is generally less expensive than panel replacement, track correction, spring work, or a complete new door. Coastal exposure, unusual door designs, and older construction can also affect the work required.

Garage door repair pricing should clearly separate labor, parts, disposal, permit-related charges if applicable, and any service call fee. A technician may charge a service call fee for diagnosis, particularly outside normal business hours. Ask whether that fee is deducted from approved repair work.

Do not select a provider solely because it advertises the lowest price. A proper inspection should show why water is entering and whether the proposed repair will address the actual source. The cheapest new seal will not solve a sloped driveway or a structurally damaged panel.

Typical Costs for Springs, Panels, Seals, and Openers

Homeowners searching for garage door spring replacement near me should understand that spring work is separate from a water-leak repair. The garage door spring cost depends on the spring type, door weight, number of springs, and labor. Torsion spring repair should be performed by a trained technician because the spring stores significant energy.

Seal replacement is usually more straightforward, while panel work costs more because the technician may need to match the section, remove hardware, balance the door, and test the opener. If the garage door opener is damaged by moisture or must be upgraded, the garage door opener installation cost includes the unit, mounting, programming, safety reversal testing, and labor.

Garage door replacement cost includes the door itself, tracks or other hardware when needed, installation, removal of the old door, and optional accessories. Ask for a detailed estimate rather than relying on a wide advertised range. This is especially important when comparing panel repair with full replacement.

Two Car Garage Door Replacement Cost Details

The 2 car garage door replacement cost is usually greater than replacing a single-car door because the door is wider, more substantial, and may require stronger hardware and more installation labor. A two car garage door replacement cost also depends on whether the opening uses one double garage door or two separate doors.

A double garage door has a large continuous span, so damage, wind exposure, and alignment can affect the complete system. Insulation, window sections, custom finishes, smart controls, and reinforced tracks increase the price. Installation labor may increase when the frame needs adjustment or the old structure has water damage.

Compare the full proposal, including measurements, hardware, opener compatibility, weather seals, threshold work, removal, warranty terms, and labor. The lowest door price may not indicate the lowest total project cost.

Do-It-Yourself Repairs Rather Than Professional Garage Door Repair

Some homeowners can perform a DIY weather seal replacement if the door is stable, the correct replacement seal is available, and the retainer is undamaged. Keep the opener disconnected only according to the manufacturer's instructions, work with the door secured, and do not force a stuck seal or remove tensioned components.

Reach out to a professional garage door technician for damaged panels, severe gaps, bent tracks, loose cables, unusual noises, or a door that is heavy or uneven. A professional can evaluate balance, alignment, rollers, hinges, safety sensors, and the opener while investigating the leak.

Never attempt torsion spring repair, cable replacement, or major track adjustment as a casual DIY project. Incorrect work can cause the door to fall or release stored energy. Emergency garage door repair is appropriate when the door is left open, has fallen off its tracks, is blocking a vehicle, or presents an immediate safety risk.

How to Find Garage Door Repair Near Me in Los Angeles

When searching for garage door repair near me, look for a local company that specifically handles leak diagnosis, weather seals, panels, frames, and drainage-related concerns. Confirm that the provider serves your part of Los Angeles and offers a clearly defined local service area. Same-day repair may be available for urgent problems, but water sealing work still requires an thorough inspection.

Choose a licensed garage door contractor and verify licensing through **Commercial Garage Door Repair & Installation in Los Angeles** the California Contractors State License Board. Ask for proof of insurance, business identification, warranty terms, and references where appropriate. A licensed garage door technician should explain whether the repair involves the door, frame, threshold, driveway, or another building component.

Before approving work, request a written repair estimate listing labor, parts, taxes, service fees, and any after-hours charges. Ask whether the quote covers testing the door after repair and whether additional damage will require authorization. These steps help Los Angeles homeowners avoid unclear garage door repair pricing.

How to Stop Future Garage Door Water Leaks

Routine garage door maintenance helps prevent water intrusion and identifies small defects before they become expensive repairs. At least once a year, inspect the bottom seal, side weatherstripping, threshold, frame, panels, hinges, rollers, and tracks. After major winter storms, check for new gaps, water marks, or movement in the door.

Maintain the garage door tracks clear and have moving hardware serviced according to the manufacturer's recommendations. Do not apply random lubricant to the bottom seal or paint over flexible weatherstripping. Replace cracked seals with materials rated for outdoor exposure and the local climate.

Maintain drainage around the garage whenever possible. Clear leaves from drains, keep downspouts directed away from the opening, and address settled concrete or standing water. A threshold can help prevent water intrusion, but it cannot replace proper grading when runoff is substantial.

Weatherproof materials, intact caulking, corrosion-resistant hardware, and an annual inspection can lengthen the life of the door. In Southern California, the best time to check seals is before the rainy season, not after the first storm exposes a leak.

Popular Questions About Garage Door Water Leaks

How can I prevent water from leaking under my garage door?

Examine the bottom weather seal, garage door threshold, floor grading, and side weatherstripping. If the seal is cracked or compressed, replace garage door seal components with the proper size. A garage door threshold seal may help when water flows across an uneven floor. If the door is out of alignment or the driveway slopes toward the garage, have a professional conduct a water leak diagnosis before determining a repair.

How much does garage door repair in Los Angeles?

Garage door repair cost depends on whether the problem involves a seal, panel, track, spring, opener, frame, or drainage issue. Garage door repair pricing can also include a service call fee, labor, parts, and emergency scheduling. Request a written garage door repair estimate with each charge identified, and evaluate the cost of repair with the likely garage door replacement cost when damage is extensive.

Do I need to replace a leaking garage door seal or the entire door?

Replace the weather seal when the door is structurally sound and the leak is confined to the bottom or edges. Consider garage door replacement when more than one panel is damaged, the frame is badly deteriorated, the door is continually misaligned, or replacement parts are difficult to find. An inspection can identify whether a seal is the real barrier failure or only one symptom of a larger problem.

Can a damaged garage door panel cause water leaks?

That's correct. A damaged garage door panel **Commercial Garage Door Repair** can have fractures, holes, bent joints, rust, or gaps that allow rainwater to enter. Panel damage can also affect door alignment and prevent the bottom seal from contacting the floor evenly. Depending on the extent and age of the door, the appropriate solution may be panel repair, panel replacement, or complete replacement.

How do I find trusted garage door repair near me in Los Angeles?

Find an trusted local provider, verify its license through the California Contractors State License Board, and confirm insurance and service coverage in your neighborhood. Choose a licensed garage door technician who performs a garage door inspection and supplies a written estimate for labor, parts, and fees. Ask specifically about same-day garage door service, warranty coverage, and experience with water leaks, older homes, and coastal conditions.